

1150/1200nm Fused WDM Coupler

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Wavelength Range Channel 1	nm	1150+/-3
Wavelength Range Channel 2	nm	1200+/-3
Insertion Loss	dB	≤1.0
Isolation	dB	≥13
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	HI1060 Flex Fiber
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST) Metal Box	(Φ)3.0x60 for Bare Fiber
		(Φ)3.0x76 for 900um Loose Tube
		(L)120x(W)12x(H)10 for 2mm/3mm Cable

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available.

ORDERING INFORMATION (PN)

FCLD-11501200-	N	- (C)	C	NN	- CC/CCC
	<i>Configuration</i>	<i>Package</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>
	1= 1x2 Type	M=Metal Box	B= 250um Bare Fiber	05=0.5m	N=Without Connector
	2= 2x2 Type	Blank for SST	L= 900um Loose Tube	10=1.0m	FC/APC=FC/APC Connector
			2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
			3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector