

1310-1650/2000nm High Power Fused WDM Coupler

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Wavelength Range Channel 1	nm	1310±20, 1550±20, 1590±20, 1625±10
Wavelength Range Channel 2	nm	1900±10, 1930±20, 1950±20, 2000±20, 2030±20, 2050±20 2070±10, 2090±10
Insertion Loss	dB	≤1.0
Isolation	dB	≥13
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	Common&2um Port	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber, NA=0.15 (O)
	1.5um Port	Same Fiber or SMF-28 Fiber
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 25, 30, 40, 50, 60, 80, 100
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	Φ3.0x ^L 60 for Bare Fiber Φ3.0x ^L 76 for 900um Loose Tube
	Metal Box	^L 120x ^W 12x ^H 10 for 2mm/3mm Cable

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLD-NN	NN	- N	(C)	(C)	-HP NN	-(C)	(C)	C	NN	-CC/CCC
Center Wavelength1	Center Wavelength2	Configuration	Mode	Fiber(λ1)	Optical Power	Package	Fiber (Com&A2)	Fiber Sleeve	Fiber Length	Connector Type
15=1550nm	90=1900nm	1= 1x2 Type	M= Mux	S= SMF-28 Fiber	1= 1W	M=Metal Box	V= SM1950 Fiber	B=Bare Fiber	05=0.5m	N=Without Connector
13=1310nm	19=1950nm	2= 2x2 Type	D= Demux	V= SM1950 Fiber	10=10W	Blank for SST	O= 10/130um DC Fiber	L=Loose Tube	10=1.0m	FC/APC=FC/APC Connector
20=2000nm	59=1590nm		Blank for Both	Blank for Same Fiber	20=20W		Blank for SMF-28 Fiber	2=2mm Cable	15=1.5m	LC/PC=LC/PC Connector
25=2050nm	62=1625nm				30=30W			3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector