

980-1150/2000nm Fused WDM Coupler

FEATURES

- ▣ Low Excess Loss
- ▣ Variety Coupling Ratio
- ▣ Epoxy-Free Optical Path
- ▣ High Reliability and Stability
- ▣ Low Profile Packaging

APPLICATIONS

- ▣ LAN WAN Systems
- ▣ Signal Monitoring
- ▣ Network Monitoring
- ▣ CATV
- ▣ Test Equipments



SPECIFICATIONS

Parameter	Unit	Value	
Wavelength Range Channel 1	nm	980±10, 1020±10, 1030±10, 1040±10, 1053±10, 1064±10, 1070±10, 1080±10, 1092±10, 1120±10, 1150±10	
Wavelength Range Channel 2	nm	1900±10, 1950±20, 2000±20, 2050±10	
Insertion Loss	dB	≤1.0	
Isolation	dB	≥13	
Optical Return Loss	dB	≥40	
Directivity	dB	≥50	
Fiber Type	-	HI1060 Fiber (H) or HI1060 Flex Fiber (F) SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O) NA=0.15	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	Φ3.0x ^L 60 for Bare Fiber
			Φ3.0x ^L 76 for 900um Loose Tube
	Metal Box		^L 120x ^W 12x ^H 10 for 2mm/3mm Cable

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. 980~1150nm transmits as low order modes in signal fiber.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLD- NN	NN	- N	(C)	(C)	- (C)	(C)	C	NN	-CC/CCC
Center Wavelength1	Center Wavelength2	Configuration	Mode	Fiber(λ1)	Package	Fiber (Com&λ2)	Fiber Sleeve	Fiber Length	Connector Type
98-980nm	90-1900nm	1- 1x2 Type	M- Mux	H- HI1060 Fiber	M- Metal Box	V- SM1950 Fiber	B- Bare Fiber	05-0.5m	N- Without Connector
03-1030nm	19-1950nm	2- 2x2 Type	D- Demux	S- SMF-28 Fiber	Blank for SST	O- 10/130um DC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
20-2000nm	06-1064nm		Blank for Both	V- SM1950 Fiber		F- HI1060 Flex Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
25-2050nm	12-1120nm			Blank for Same Fiber		Blank for SMF-28 Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector