

980/1030nm Fused WDM Coupler

FEATURES

- ☑ Low Excess Loss
- ☑ Variety Coupling Ratio
- ☑ Epoxy-Free Optical Path
- ☑ High Reliability and Stability
- ☑ Low Profile Packaging

APPLICATIONS

- ☑ LAN WAN Systems
- ☑ Signal Monitoring
- ☑ Network Monitoring
- ☑ CATV
- ☑ Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength 1	nm	976, 980
Center Wavelength 2	nm	1030, 1036
Bandwidth	nm	+/-5
Insertion Loss	dB	≤0.8
Isolation	dB	≥13
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	HI1060 Fiber or HI1060 Flex Fiber (F) 10/125um SC Fiber (E) or 10/125um DC Fiber (O) NA=0.075
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package	Stainless Steel Tube (SST)	mm
Dimension	Metal Box	
		Φ3.0x ^L 60 for Bare Fiber
		Φ3.0x ^L 76 for 900um Loose Tube
		^L 120x ^W 12x ^H 10 for 2mm/3mm Cable

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

4. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLD-NN	NN	- N	(C)	(C)	-(C)	(C)	C	NN	-CC/CCC
Wavelength1	Wavelength2	Configuration	Mode	Fiber(λ1)	Package	Fiber (Com&λ2)	Fiber Sleeve	Fiber Length	Connector Type
98- 980nm	03-1030nm	1- 1x2 Type	M- Mux	I- HI1060 Fiber	M- Metal Box	F- HI1060 Flex Fiber	B- Bare Fiber	05-0.5m	N- Without Connector
97- 976nm	36-1036nm	2- 2x2 Type	D- Demux	F- HI1060 Flex Fiber	Blank for SST	E- 10/125um SC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
03-1030nm	98- 980nm		Blank for Both	Blank for Same Fiber		O- 10/125um DC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
36-1036nm	97- 976nm					Blank for HI1060 Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector