

750~850nm 1X6/2X6 Fused Fiber Splitter Module for Pulse Power

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	1X6/2x6
Center Wavelength	nm	750, 780, 793, 808, 830, 850
Passband Width	nm	+/-10
Insertion Loss	dB	≤10.3
PDL	dB	≤0.3
Uniformity	dB	≤1.8
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	HI780 Fiber or 780-HP Fiber
Fiber Tensile Load	N	5
Maximum Average Power	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(L)100x(W)80x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLT- NNN	-	NXN	-H NN	P NN	-(C)	C	NN	- CC/CCC
<i>Center Wavelength</i>		<i>Configuration</i>	<i>Average Power</i>	<i>Peak Power</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>
780-780nm		1X6- 1x6 Type	03- 300mW	01- 100W	7-780HP Fiber	B- Bare Fiber	05-0.5m	N-Without Connector
808-808nm		2X6- 2x6 Type	2- 2W	2- 2kW	Blank for HI780 Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
850-850nm			5- 5W	5- 5kW		2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
830-830nm			10-10W	10-10kW		3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector