

750~850nm Filter Splitter Module

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	1x4 or 2x4 or 4x4	1x8 or 2x8 or 4x8
Center Wavelength	nm	750, 780, 793, 808, 830, 850	
Bandwidth	nm	+/-15nm or customer specify	
Insertion Loss	Typ.	dB	11.3
	Max.	dB	12.0
Uniformity	dB	≤1.0	≤1.2
PDL	dB	≤0.20	
Optical Return Loss	dB	≥50	
Directivity	dB	≥50	≥45
Fiber Type	-	HI780 Fiber or 780HP Fiber	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	L100xW80xH10	

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFFM	-	NNN	-	NxN	-	(C)	C	NN	-CC/CCC
<i>Wavelength</i>		<i>Configuration</i>		<i>Fiber Type</i>		<i>Fiber Sleeve</i>		<i>Fiber Length</i>	<i>Connector Type</i>
780~780nm		1X4-1X4 Type		7- 780HP Fiber		B- Bare Fiber		05-0.5m	N-Without Connector
793~793nm		1X8-1X8 Type		Blank for HI780 Fiber		L- Loose Tube		10-1.0m	FC/APC=FC/APC Connector
808~808nm		2X4-2X4 Type				2- 2mm Cable		15-1.5m	LC/PC=LC/PC Connector
850~850nm		4X8-4X8 Type				3- 3mm Cable		20-2.0m	SC/UPC=SC/UPC Connector