

2000nm Fiber Mirror

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength	nm	1900, 1950, 2000, 2050
Bandwidth	nm	+/-20
Insertion Loss (Max.)	dB	1.0
PDL (for SM Fiber Type)	dB	≤0.10
Extinction Ratio (for PM Fiber Type)	dB	≥20
Fiber Type	SM Fiber Type	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O) or 25/250um DC Fiber (R)
	PM Fiber Type	PM1550 Panda Fiber or PM1950 Fiber (V) 10/130um PMDC Fiber (O) or 25/250um PMDC Fiber (R)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(Φ)5.5x35

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFMR-	NNNN	-	C	(C)	C	NN	-	CC/CCC
	<i>Center Wavelength</i>		<i>Fiber Type</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
	1900=1900nm		P= PM Fiber	V=SM1950 or PM1950 Fiber	B= Bare Fiber	05=0.5m		N=Without Connector
	1950=1950nm		S=SM Fiber	O=10/130 DC or PMDC Fiber	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
	2000=2000nm			R=25/250 DC or PMDC Fiber	2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
	2050=2050nm			Blank for SMF-28 Fiber or PM1550 Fiber	3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector