

900-960nm Fiber Mirror

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength	nm	915, 930, 940, 950	
Bandwidth	nm	+/-10	
Insertion Loss (Max.)	dB	1.2	
PDL (for SM Fiber Type)	dB	≤0.20	
Extinction Ratio (for PM Fiber Type)	dB	≥20	
Fiber Type	SM Fiber Type	-	HI780 Fiber, HI1060 Fiber or 10/125um SC Fiber (E)
		-	10/125um DC Fiber (O), 15/130um DC Fiber (W)
		-	20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
	PM Fiber Type	-	PM850 Fiber, PM980 Fiber or PM1060L Fiber (E)
		-	10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W)
		-	20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package	Stainless Steel Tube (SST)	mm	(Φ)5.5x35
Dimension	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFMR-	NNN	-	C	(C)	(C)	C	NN	-CC/CCC
<i>Center Wavelength</i>			<i>Fiber Type</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>
915-915nm			P= PM Fiber	M= Metal Box	H=HI1060 or PM980 Fiber	B= Bare Fiber	05=0.5m	N =Without Connector
930-930nm			S=SM Fiber	Blank for SST	E=10/125 SC or PM1060L Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
940-940nm					R=25/250 DC or PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC =LC/PC Connector
950-950nm					Blank for HI780 or PM850 Fiber	3= 3mm Cable	20=2.0m	SC/UFC=SC/UFC Connector