

1310~1590nm Partial Reflective Faraday Mirror

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength (CW)	nm	1310, 1480, 1550, 1590
Bandwidth	nm	+/-15
Excess Loss	dB	≤1.0
Nominal Reflective Ratio	%	1±0.5, 2±0.4, 5±1, 10±2, 50±8, 80, 90
Faraday Rotation Angle (Transmission)	Deg	22.5, 45, 90
Rotation Angle Tolerance (CW. 23°C)	Deg	≤+/-3
Faraday Position	Forward Type	-
	Backward Type	-
		Faraday is before the Mirror
		Faraday is after the Mirror
PDL (for SM Fiber Type)	dB	≤0.15
Extinction Ratio (for PM Fiber Type)	dB	≥20
Fiber Type	SM Fiber Type	-
	PM Fiber Type	-
		SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)
		PM1310/1550 Panda Fiber or 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~70
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm
	Metal Box	mm
		(Ø)5.5x35
		(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFPM-NNNN-NN (NN) - (C) C C - (C) (C) C NN - CC/CCC
<i>Center Wavelength Ref. Ratio Rotation Angle Faraday Position Input Fiber Output Fiber Package Fiber Type Fiber Sleeve Fiber Length Connector Type</i>
1310-1310nm 01-1% 90-90degree B-Backward S-SM Fiber S-SM Fiber M-Metal Box O-10/130DC or 10/125PMDC Fiber B- Bare fiber 05-0.5m N-Without Connector
1480-1480nm 10-10% 225-22.5degree Blank for Forward P-PM Fiber P- PM Fiber Blank for SST T-12/130DC or PMDC Fiber L- Loose Tube 10-1.0m FC/APC=FC/APC Connector
1550-1550nm 50-50% Blank for 45degree G-25/300 DC or PMDC Fiber 2- 2mm Cable 15-1.5m LC/PC=LC/PC Connector
1590-1590nm 80-80% Blank for SMF-28 Fiber 3- 3mm Cable 20-2.0m SC/UPC=SC/UPC Connector
or PM1310/1550 Fiber