

915/1020-1120nm High Power WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters		Unit	Value
Pass Channel Wavelength Range λ_1		nm	915 \pm 10, 1020 \pm 5, 1030 \pm 10, 1040 \pm 10, 1053 \pm 10, 1064 \pm 10, 1070 \pm 10, 1080 \pm 10, 1092 \pm 5, 1120 \pm 5
Reflective Channel Wavelength Range λ_2		nm	
Insertion Loss	Pass Channel@ λ_1	dB	\leq 1.2
	Reflective Channel@ λ_2	dB	\leq 1.0
Configuration	Y Type	-	3-port
	X Type	-	4-port (2x2 WDM)
Isolation	Pass Channel@ λ_2	dB	\geq 25
	Reflective Channel@ λ_1	dB	\geq 12
Optical Return Loss		dB	\geq 45
Directivity		dB	\geq 50
Polarization Dependent Loss		dB	\leq 0.2
Fiber Type		-	HI780 Fiber, HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
Fiber Tensile Load		N	5
Maximum Optical Power (CW)		W	1, 2, 3, 5, 10, 15, 20
Operating Temperature		$^{\circ}$ C	0~50
Storage Temperature		$^{\circ}$ C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35 (\leq 5W); (\varnothing)6.0x48 (5~10W)
	Metal Box	mm	(L)90x(W)18x(H)10 (>10W); (L)120x(W)12x(H)10 (\leq 10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFWM-	NN	NN	- (C)	- HP NN	-(C)	(C)	C	NN	-CC/CCC
Ref Wavelength	Pass Wavelength	Configuration	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
03= 1030nm	91=915nm	X=X Type	1=1W	M=Metal Box	H=HI1060 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector	
06= 1064nm	05=1053nm	Blank for Y Type	5=5W	Blank for SST	E=10/125 SC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector	
12=1120nm	03=1030nm		10=10W	or >10W	R=25/250 DC Fiber	2=2mm Cable	15=1.5m	LC/PC=LC/PC Connector	
91=915nm	09=1092nm		20=20W		Blank for HI780 Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector	