

915/980nm High Power WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value
Pass Channel Wavelength Range λ_1	nm	970~990
Reflective Channel Wavelength Range λ_2	nm	910~920
Insertion Loss	Pass Channel@ λ_1	≤1.2
	Reflective Channel@ λ_2	≤1.0
Configuration	Y Type	3-port
	X Type	4-port (2x2 WDM)
Isolation	Pass Channel@ λ_2	≥25
	Reflective Channel@ λ_1	≥12
Optical Return Loss	dB	≥45
Directivity	dB	≥50
Polarization Dependent Loss	dB	≤0.2
Fiber Type	-	HI780 Fiber, HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm (Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~10W)
	Metal Box	mm (L)90x(W)12x(H)10 (>10W); (L)120x(W)12x(H)10 (≤10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFWM-	NN	NN	- (C)	- HP NN	- (C)	(C)	C	NN	-CC/CCC
Ref Wavelength	Pass Wavelength	Configuration	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
91-915nm	98-980nm	X=X Type Blank for Y Type	1-1W 5-5W 10-10W 20-20W	M=Metal Box Blank for SST or >10W	H=HI1060 Fiber E=10/125 SC Fiber R=25/250 DC Fiber Blank for HI780 Fiber	B= Bare Fiber L= Loose Tube 2=2mm Cable 3=3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector	