

1570nm Bandpass Filter/Isolator Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks



SPECIFICATIONS

Parameters	Unit	Single Stage	Dual Stage
Center Wavelength	nm	1570	
Min. Pass Band Width @ 0.5dB	nm	4.0, 9.0, 15.0	
Stop Band @25dB	4nm Bandwidth	1520~1556 & 1574~1610	
	9nm Bandwidth	1520~1560 & 1580~1610	
	15nm Bandwidth	1520~1557 & 1583~1610	
Insertion Loss@23°C	dB	≤1.3	≤1.5
Signal Isolation (23°C)	dB	≥25	≥40
Configuration	D Type	2-port	
	Y Type	3-port, (Blocked Wavelength Guide Out)	
	X Type	4-port, (Both Block Wavelength Guide Out)	
Fiber Type at 3 rd or 4 th Port (Y/X Type)	-	Same Fiber of other ports or 50/125um MM Fiber	
ASE Direction	Forward Type	Bandpass Filter is before isolator	
	Backward Type	Bandpass Filter is after isolator	
	Twin Type	Bandpass Filter is at both sides of isolator	
Optical Return Loss	dB	≥45	
PDL	dB	≤0.2	
Fiber Type	-	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package	Stainless Steel Tube (SST)	mm (Ø)5.5x35	
Dimension	Metal Box	mm (L)120x(W)12x(H)10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. Suggest to use Y or X type if blocked optical power is >1W.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FHBI-1570-C	NN	C	-	(C)	(C)	-	(C)	C	NN	-CC/CCC
<i>Stage</i>	<i>Bandwidth</i>	<i>ASE Type</i>	<i>3rd Port Fiber</i>	<i>4th Port Fiber</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>	
S= Single Stage	40=4nm	F= Forward	Y=Same Fiber	Y=Same Fiber	M=Metal Box	O=10/130 DC Fiber	B= Bare fiber	05=0.5m	N=Without Connector	
D= Dual Stage	90=9nm	B=Backward	5=50/125um Fiber	5=50/125um Fiber	Blank for SST	T=12/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector	
	150=15nm	T=Twin	Blank for D Type	Blank for D&Y Type		G=25/300 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector	
						Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector	