

1030nm PM Bandpass Filter/Isolator Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters	Unit	Single Stage	Dual Stage
Center Wavelength	nm	1030	
Min. Pass Band Width @ 0.5dB	nm	1.3, 2.0, 4.0, 6.0, 9.0, 12, 20	
Stop Wavelength (ASE)	1.3nm Bandwidth	nm	1000~1027&1033~1100
	2nm Bandwidth	nm	1000~1026&1034~1100
	4nm Bandwidth	nm	1000~1025&1035~1100
	6nm Bandwidth	nm	1000~1023&1037~1100
	9nm Bandwidth	nm	1000~1021&1039~1100
	12nm Bandwidth	nm	1000~1018&1042~1100
	20nm Bandwidth	nm	960~1014&1046~1100
Insertion Loss@23°C	dB	≤3.8	≤7.5
Signal Isolation (23°C)	dB	≥20	≥40
Stop Wavelength (ASE) Isolation	Standard	dB	≥25
	High Isolation	dB	≥45
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥45	
Extinction Ratio	dB	≥20	
Work Mode	S Type	-	Can only work in slow axis
	F Type	-	Can work both in slow axis and fast axis
Fiber Type	Input&Output	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L)
		-	10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W)
	ASE Guide Out (Y/X Type)	-	20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
		-	Same Fiber, Corr. SM Fiber or MM Fiber
Max. Optical Power (CW)	mW	50	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	Φ5.5xL35
	Metal Box	mm	L120xW12xH10

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Only guarantee 50mW continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

Stage	Bandwidth	ASE Type	ASE Iso	Work Mode	Fwd ASE Fiber	Bwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
S= Single Stage	20~2nm	B=Backward	I=High	S= S Type	Y=Same Fiber	Y=Same Fiber	M=Metal Box	2=PM980Fiber	B= Bare fiber	05=0.5m	N=Without Connector
D= Dual Stage	60~6nm	T=Two-way	Isolation	F= F Type	A=105/125um Fiber	A=105/125um Fiber	Blank for SST	E=PM1060L Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	90~9nm	Blank for Forward	Blank for		N=None	5=50/125um Fiber		Q=20/130 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	200~20nm		Standard		Blank for D Type	Blank for None/D Type		R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

