

# 1540nm BP/Partial Mirror Hybrid

## FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

## APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



## SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1540	
Min. Bandwidth@0.5dB	nm	2.0, 4.0, 5.0, 7.0, 10.0, 15.0	
Excess Loss	dB	≤1.3	
Stop Band @25dB	2nm Bandwidth	1510~1538 & 1542~1600	
	4nm Bandwidth	1510~1536 & 1544~1600	
	5nm Bandwidth	1510~1534 & 1546~1600	
	7nm Bandwidth	1510~1533 & 1547~1600	
	10nm Bandwidth	1510~1530 & 1550~1600	
	15nm Bandwidth	1510~1527.5 & 1552.5~1600	
Reflective Ratio	%	1±0.6, 2±0.8, 5±1, 10, 20, 30, 40, 50, 80, 90	
Configuration	D Type	2-port	
	Y Type	3-port, (Blocked Wavelength Guide Out)	
Fiber Type at 3 <sup>rd</sup> Port (Only for Y Type)	-	Same Fiber or 50/125um MM Fiber	
Optical Return Loss	dB	≥45	
PDL	dB	≤0.15	
Fiber Type	-	SMF-28 Fiber or 10/130um DC Fiber (O)	
	-	12/130um DC Fiber (T) or 20/130um DC Fiber (Q)	
	-	25/250um DC Fiber (R) or 25/300um DC Fiber (G)	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
  3. Suggest to use Y type if blocked optical power is >1W.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

## ORDERING INFORMATION (PN)

FHBR-NNNN	NN	NN	(C)	(C)	(C)	C	NN	-CC/CCC
Center Wavelength	Bandwidth	Ref. Ratio	3rd Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1540=1540nm	20=2nm	01=1%	Y=Same Fiber	M=Metal Box	O=10/130 DC Fiber	B= Bare fiber	05=0.5m	N=Without Connector
	50=5nm	05=5%	5=50/125um Fiber	Blank for SST	T=12/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	100=10nm	50=50%	Blank for D Type		G=25/300 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	150=15nm	90=90%			Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector