

2090nm BP/Partial Mirror Hybrid for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value
Center Wavelength	nm	2090
Min. Bandwidth@0.5dB	nm	20.0
Excess Loss	dB	≤1.8
Stop Band @25dB	nm	2030-2070 & 2110-2150
Reflective Ratio	%	1±0.6, 2±0.8, 5±1, 10, 20, 30, 40, 50, 80, 90
Configuration	D Type	2-port
	Y Type	3-port, (Blocked Wavelength Guide Out)
Fiber Type at 3 rd Port (Only for Y Type)	-	Same Fiber or 50/125um MM Fiber
Optical Return Loss	dB	≥45
PDL	dB	≤0.15
Fiber Type	-	SMF-28 Fiber or SM1950 Fiber (V)
	-	10/130um DC Fiber (O) or 25/250um DC Fiber (R)
Fiber Tensile Load	N	5
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5, 10
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm (Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~8W)
	Metal Box	mm (L)90x(W)18x(H)10 (>8W); (L)120x(W)12x(H)10 (≤8W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. Suggest to use Y type if blocked optical power is >1W.
 4. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FHBR-NNNN-NNN	NN	-(C)	-H NN	P	NN	-(C)	(C)	C	NN	-CC/CCC		
Center Wavelength	Bandwidth	Ref. Ratio	3rd Port Fiber	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type		
2090	2090nm	200	20nm	01=1%	Y=Same Fiber	03=300mW	01=100W	M=Metal Box	V=SM1950 Fiber	B= Bare fiber	05=0.5m	N=Without Connector
		05=5%	5=50/125um Fiber	1= 1W	1= 1kW	Blank for SST	0=10/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector		
		50=50%	Blank for D Type	5= 5W	5= 5kW	or >8W	R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector		
		90=90%		10=10W	10=10kW		Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector		