

2000nm Optical Inline Polariser

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation
- Research Labs



SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength	nm	1950, 2000	1900, 2050
Bandwidth	nm	+/-30	+/-20
Insertion Loss @ 23°C	(Typ.)	dB	
	(Max.)	dB	
Extinction Ratio @ 23°C	(Typ.)	dB	
	(Min.)	dB	
Optical Return Loss	dB	≥50	
Configuration	D Type	-	
	Y Type	-	
Fiber Type at 3 rd Port (Only for Y Type)	-	Same Fiber, Corr. SM Fiber or 50/125um MM Fiber	
Fiber Type	SM Fiber	-	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O), 25/250um DC Fiber (R)
	PM Fiber	-	PM1550 Panda Fiber or PM1950 Fiber (V) 10/130um PMDC Fiber (O), 25/250um PMDC Fiber (R)
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x35
	Metal Box	mm	L120x ^W 12x ^H 10

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different fiber type, configuration and optical power

ORDERING INFORMATION (PN)

FILP-NNNN	-	C	C	(C)	- (C)	(C)	C	NN	- CC/CCC
Center Wavelength	Input Fiber	Output Fiber	3rd Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
1900~1900nm	P= PM Fiber	P= PM Fiber	P= Same Fiber	M= Metal Box	V=SM1950 or PM1950 Fiber	B= Bare fiber	05=0.5m	N=Without Connector	
1950~1950nm	S=SM Fiber	S=SM Fiber	S=Corr. SM Fiber	Blank for SST	O=10/130 DC or PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector	
2000~2000nm			S=50/125um MM Fiber		R=25/250 DC or PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector	
2050~2050nm			Blank for D Type		Blank for SMF-28 Fiber or PM1550 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector	