

1092nm Multimode Bandpass Filter

FEATURES

- ▣ High Isolation
- ▣ Low Insertion Loss
- ▣ High Reliability and Stability
- ▣ Various Bandwidth
- ▣ High Optical Power

APPLICATIONS

- ▣ Broadband Systems
- ▣ Optical Amplifying Systems
- ▣ Telecommunication Networks
- ▣ Laser Systems
- ▣ Research Labs



SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1092	
Min. Pass Band Width @ 0.5dB	nm	8.0	
Insertion Loss over Pass Band Wavelength	dB	≤1.2	
Stop Wavelength (ASE)	nm	1000~1084&1100~1150	
Stop Wavelength (ASE) Standard	dB	≥25	
Isolation High Isolation	dB	≥45	
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥30	
Fiber Type	Input&Output	-	
			50/125um or 62.5/125um MM Fiber
			50/125um MM OM3 Fiber
	ASE Guide Out (Y/X Type)	-	105/125um MM Fiber
		-	Same Fiber
Fiber Tensile Load	N	5	
Max. Optical Power (CW, ASE+Signal)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5xL35
	Metal Box	mm	L120xW12xH10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 3. Specifications are tested at low order modes.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available.
 - 5 Package size may be different for different fiber type, optical power and configurations.

ORDERING INFORMATION (PN)

FMBP-1092-NN(C)					(C)	(C)	(C)	-(C)	C	C	NN	-CC/CCC
Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Dwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type			
80~8nm	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	M=Metal Box	5= 50/125um MM Fiber	B= Bare fiber	05=0.5m	N=Without Connector			
	T=Two-way	Isolation	N=None	Blank for None or D Type	Blank for SST	6= 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector			
	Blank for Forward	Blank for	Blank for D Type			3= OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector			
		Standard				A= 105/125um, NA=0.22	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector			
						B=105/125um, NA=0.15						