

915/980nm Multimode WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Add/Drop Multiplexing
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value	
Pass Channel Wavelength Range λ_1	nm	970~990	
Reflective Channel Wavelength Range λ_2	nm	910~920	
Insertion Loss	Pass Channel@ λ_1	dB	≤ 1.2
	Reflective Channel@ λ_2	dB	≤ 1.0
Configuration	Y Type	-	3-port
	X Type	-	4-port (2x2 WDM)
Isolation	Pass Channel@ λ_2	dB	≥ 25
	Reflective Channel@ λ_1	dB	≥ 12
Optical Return Loss	dB	≥ 30	
Directivity	dB	≥ 35	
Fiber Type	-	50/125um or 62.5/125um MM Fiber 50/125um MM OM3 Fiber 105/125um MM Fiber	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:** 1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available.
 4. Specifications are tested at low order modes.
 5. Devices with other wavelength range are also available per request.

ORDERING INFORMATION (PN)

FMFM-	NN	NN	(C)	- (C)	C	C	NN	- CC/CCC
<i>Ref Wavelength</i>	<i>Pass Wavelength</i>	<i>Configuration</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>	
91-915nm	98-980nm	X- X Type Blank for Y Type	M= Metal Box Blank for SST or >10W	5- 50/125um MM Fiber 6- 62.5/125um MM Fiber 3- OM3 MM Fiber A- 105/125um, NA=0.22 B- 105/125um, NA=0.15	B- Bare Fiber L- Loose Tube 2- 2mm Cable 3- 3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector	