

750~850nm PBC/PBS for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Research Labs
- Laser Systems



SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength	nm	760, 780, 793, 808	830, 850
Bandwidth	nm	+/-10	
Insertion Loss	(Typ.)	dB	0.9
	(Max.)	dB	1.5
Directivity	dB	≥50	
Optical Return Loss	dB	≥45	
Extinction Ratio (for FPBS)	(Typ.)	dB	22
	(Min.)	dB	18
Fiber Type of Port 1 & Port 2	-	PM850 Fiber or PM780-HP Fiber	
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1
Direction of Incident Polarization	-	Slow Axis	
Fiber Tensile Load	N	5	
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5 10, 15, 20	
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)
	Metal Box	mm	^L 90x ^W 12x ^H 10 (>10W); ^L 120x ^W 12x ^H 10 (≤10W)

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN) FPBC=Polarization Beam Combiner; FPBS=Polarization Beam Splitter.

FPBC FPBS	NNN	C	H	NN	P	NN	(C)	C	C	NN	CC/CCC
	Center Wavelength	3rd Port Fiber		Average Power	Peak Power	Package		Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	780-780nm	S=S Type		03-300mW	01-100W	M=Metal Box		2-PM850 Fiber	B= Bare fiber	05-0.5m	N=Without Connector
	793-793nm	P=P Type		1- 1W	1- 1kW	Blank for SST		7-PM780HP Fiber	L= Loose Tube	10-1.0m	FC/APC=FC/APC Connector
	830-830nm	Q=Q Type		5- 5W	5- 5kW	or >10W			2= 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
	850-850nm			10-10W	10-10kW				3= 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector