

1080nm High Power PM Bandpass Filter

FEATURES

- ☑ High Isolation
- ☑ Low Insertion Loss
- ☑ High Reliability and Stability
- ☑ Various Bandwidth
- ☑ High Optical Power

APPLICATIONS

- ☑ Broadband Systems
- ☑ Optical Amplifying Systems
- ☑ Telecommunication Networks
- ☑ Laser Systems
- ☑ Research Labs



SPECIFICATIONS

| Parameters | Unit | Standard | High ER Type |
|------------------------------------------|----------------------------|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Center Wavelength | nm | 1080 | |
| Min. Pass Band Width @ 0.5dB | nm | 5.0 | |
| Insertion Loss over Pass Band Wavelength | dB | ≤1.2 | ≤1.4 |
| Stop Wavelength (ASE) | nm | 1030-1070&1090-1150 | |
| Stop Wavelength (ASE) Standard | dB | ≥25 | |
| Isolation High Isolation | dB | ≥45 | |
| ASE Direction | - | F: Forward, B: Backward, T: Two-way | |
| Configuration | - | D: 2-port, Y: 3-port, X: 4-port | |
| Optical Return Loss | dB | ≥50 | |
| Extinction Ratio | dB | ≥18 | ≥20 |
| Fiber Type | Input&Output | - | PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R) |
| | ASE Guide Out (Y/X Type) | - | Same Fiber, Corr. SM Fiber or MM Fiber |
| Fiber Tensile Load | N | 5 | |
| Max. Optical Power (CW, ASE+Signal) | W | 1, 2, 3, 5, 10, 15, 20, 30, 40, 05, 60, 80, 100 | |
| Max. ASE Optical Power (CW) | W | 0.3, 0.5, 1, 2, 3, 4, 5, 10 | |
| Operating Temperature | °C | 0~50 | |
| Storage Temperature | °C | -40~85 | |
| Package Dimension | Stainless Steel Tube (SST) | mm | ∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W) |
| | Metal Box | mm | ^L 90x ^W 12x ^H 10 (>10W); ^L 120x ^W 12x ^H 10 (≤10W) |

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. High ER type can only work in slow axis; Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
 4. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 6. Package size may be different for different fiber type, optical power and configurations.

ORDERING INFORMATION (PN)

FPBP-1080-NN(C) (C) (C) (C) (C) -HP NN -(NN) -(C) C C NN -CC/CCC

| Bandwidth | Type | ASE Type | ASE Iso | Fwd ASE Fiber | Bwd ASE Fiber | Optical Power | ASE Power | Package | Fiber Type | Fiber Sleeve | Fiber Length | Connector Type |
|-----------|-----------|-------------------|------------------|------------------|--------------------------|---------------|-----------------|---------------|---------------------|---------------|--------------|-------------------------|
| 50=5nm | R=High ER | B=Backward | I=High | Y=Same Fiber | Y=Same Fiber | 1=1W | 1=1W | M=Metal Box | 2=PM980Fiber | B= Bare fiber | 05=0.5m | N=Without Connector |
| | Blank for | T=Two-way | Isolation | S=Corr. SM Fiber | S=Corr. SM Fiber | 5=5W | 5=5W | H=H Box | E=PM1060L Fiber | L= Loose Tube | 10=1.0m | FC/APC=FC/APC Connector |
| | Standard | Blank for Forward | Blank for | N=None | A=105/125um Fiber | 10=10W | 10=10W | Blank for SST | Q=20/130 PMDC Fiber | 2= 2mm Cable | 15=1.5m | LC/PC=LC/PC Connector |
| | | Standard | Blank for D Type | Blank for D Type | Blank for None or D Type | 20=20W | Blank for 300mW | | R=25/250 PMDC Fiber | 3= 3mm Cable | 20=2.0m | SC/UPC=SC/UPC Connector |