

## 2051nm High Power PM Bandpass Filter

### FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



### SPECIFICATIONS

Parameters		Unit	Standard	High ER Type
Center Wavelength		nm	2051	
Min. Pass Band Width @ 0.5dB		nm	5.0	
Insertion Loss over Pass Band Wavelength		dB	≤1.4	≤1.6
Stop Wavelength (ASE)		nm	1970-2040 & 2062-2100	
Stop Wavelength (ASE)	Standard	dB	≥25	
Isolation	High Isolation	dB	≥45	
ASE Direction		-	F: Forward, B: Backward, T: Two-way	
Configuration		-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss		dB	≥50	
Extinction Ratio		dB	≥18	≥20
Fiber Type	Input&Output	-	PM1550 Panda Fiber or PM1950 Fiber (V)	
	ASE Guide Out (Y/X Type)	-	10/130um PMDC Fiber (O) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load		N	5	
Max. Optical Power (CW, ASE+Signal)		W	1, 2, 3, 5, 10, 15, 20	
Max. ASE Optical Power (CW)		W	0.3, 0.5, 1, 2, 3, 4, 5, 10	
Operating Temperature		°C	0~50	
Storage Temperature		°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5xL35 (≤5W); ∅6.0xL50 (5~10W)	
	Metal Box	mm	H: L90xW12xH10 (>10W); M: L120xW12xH10 (≤10W)	

**Note:** 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. High ER type can only work in slow axis; Suggest to use Y/X type or H Box if blocked optical power is ≥1W.

4. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.

5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of

Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

6. Package size may be different for different optical power and configurations.

### ORDERING INFORMATION (PN)

FPBP-2051-NN(C)(C) (C) (C) (C) - HPNN -(NN) -(C) C C NN -CC/CCC												
Bandwidth	Type	ASE Type	Fwd ASE Fiber	ASE Iso	Dwd ASE Fiber	Optical Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
50-5nm	R=High ER	B=Backward	Y=Same Fiber	I=High	Y=Same Fiber	1-1W	1-1W	M=Metal Box	2-PM1550Fiber	B= Bare fiber	05-0.5m	N=Without Connector
	Blank for	T=Two-way	S=Corr. SM Fiber	Isolation	S=Corr. SM Fiber	3-3W	5-5W	H=H Box	Y-PM1950 Fiber	L= Loose Tube	10-1.0m	FC/APC=FC/APC Connector
	Standard	Blank for Forward	N=None	Blank for	A=105/125um Fiber	5-5W	10-10W	Blank for SST	O=10/130 PMDC Fiber	2= 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
		Blank for D Type	Standard	Blank for None or D Type	10-10W	Blank for 300mW			R=25/250 PMDC Fiber	3= 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector