

760-850/900~990nm High Power Fused PM WDM Coupler

FEATURES

- ▣ Low Excess Loss
- ▣ Variety Coupling Ratio
- ▣ Epoxy-Free Optical Path
- ▣ High Reliability and Stability
- ▣ Low Profile Packaging

APPLICATIONS

- ▣ LAN WAN Systems
- ▣ Signal Monitoring
- ▣ Network Monitoring
- ▣ CATV
- ▣ Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength 1	nm	760, 780, 793, 808, 830, 850
Center Wavelength 2	nm	915, 930, 950, 980
Bandwidth	nm	+/-2
Insertion Loss	dB	≤1.0
Isolation	dB	≥13
Extinction Ratio	dB	≥18
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	PM780 Fiber (7) or PM850 Fiber PM980 Fiber (H) or PM1060L Fiber (E)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 25, 30
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST) Metal Box	mm
		φ3.0x ^L 60 for Bare Fiber
		φ3.0x ^L 76 for 900um Loose Tube
		^L 120x ^W 12x ^H 10 for 2mm/3mm Cable

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.

4. 750~850nm may transmit as low order modes in signal fiber.

5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

6. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FPCD	NN	-N	(C)	(C)-HP	NN	-(C)	(C)	C	NN	-CC/CCC
Wavelength1	Wavelength2	Configuration	Mode	Fiber(λ1)	Optical Power	Package	Fiber (Com&λ2)	Fiber Sleeve	Fiber Length	Connector Type
78~780nm	91~915nm	1- 1x2 Type	M= Mux	5- Corr. SM Fiber	1- 1W	M= Metal Box	7- PM780-HP Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
79~793nm	93~930nm	2- 2x2 Type	D= Demux	7- PM780-HP Fiber	5- 5W	Blank for SST	H=PM980 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
95~950nm	83~830nm		Blank for Both	I=HI780 Fiber	10=10W		E=PM1060L Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
98~980nm	85~850nm			Blank for Same Fiber	30= 30W		Blank for PM850 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector