

900~950nm High Power PM Filter Splitter Module

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	1x4 or 2x4 or 4x4	1x8 or 2x8 or 4x8
Center Wavelength	nm	915, 930, 940, 950	
Bandwidth	nm	+/-15nm or customer specify	
Insertion Loss	Typ.	dB	7.5
	Max.	dB	8.1
Uniformity	dB	≤1.0	≤1.2
Extinction Ratio	B Type	dB	≥18
	F Type	dB	≥20
Working Mode	B Type	dB	Can work both in Fast Axis and Slow Axis
	F Type	dB	Can only work in Slow Axis and Fast Axis is blocked
Optical Return Loss	dB	≥50	
Directivity	dB	≥50	≥45
Fiber Type	-	PM850 Fiber, PM980 Fiber or PM1060L Fiber (E) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 30, 50, 60	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	L160x ^W 140x ^H 10	L160x ^W 160x ^H 10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power fiber type and configurations.

ORDERING INFORMATION (PN)

FPFM- NNN	- NxN	(C)	- HPNN	- C	C	NN	- CC/CCC
Wavelength	Configuration	Type	Optical Power	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915~915nm	1X4~1X4 Type	B=B Type	1~1W	2~PM850Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
930~930nm	1X8~1X8 Type	Blank for F Type	3~3W	H~PM980 Fiber	L= Loose Tube	10~1.0m	FC/APC=FC/APC Connector
940~940nm	2X4~2X4 Type		5~5W	E~PM1060L Fiber	2= 2mm Cable	15~1.5m	LC/PC=LC/PC Connector
950~950nm	4X8~4X8 Type		10~10W	R~25/250 PMDC Fiber	3= 3mm Cable	20~2.0m	SC/UPC=SC/UPC Connector