

975~1160nm 1x10 PM Filter Splitter Module

FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab



SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength	nm	975, 980, 990, 1000 1020, 1030, 1040, 1053, 1064 1070, 1080, 1092, 1103, 1120, 1150
Bandwidth	nm	+/-20nm or customer specify
Configuration	-	1x10 or 2x10
Insertion Loss	dB	≤13.6
Uniformity	dB	≤1.8
Extinction Ratio	dB	≥20
Optical Return Loss	dB	≥50
Working Mode	-	Can only work in Slow Axis
Fiber Type	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
Alignment	-	Slow Axis
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	^L 160x ^W 160x ^H 10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. The devices can only work in slow axis and fast axis is blocked.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPFM-	NNNN	-	NxNN	-	C	C	NN	-	CC/CCC
	<i>Wavelength</i>		<i>Configuration</i>		<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
	975~975nm		1X10~1X10 Type		2~PM980Fiber	B= Bare Fiber	05~0.5m		N=Without Connector
	1030~1030nm		2X10~2X10 Type		E~PM1060L Fiber	L= Loose Tube	10~1.0m		FC/APC=FC/APC Connector
	1064~1064nm				Q=20/130 PMDC Fiber	2= 2mm Cable	15~1.5m		LC/PC =LC/PC Connector
	1120~1120nm				R=25/250 PMDC Fiber	3= 3mm Cable	20~2.0m		SC/UPC=SC/UPC Connector