

1500~1600/2000nm WDM/Iso/Tap PM Hybrid Filter

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks



SPECIFICATIONS

Parameters		Unit	Single Stage	Dual Stage
Signal Wavelength Range λ_1		nm	2000+/-20	
Pump Wavelength Range λ_2		nm	1530±20, 1550±20, 1570±20, 1590±20	
Excess Loss	Signal Channel@ λ_1	dB	≤1.8	≤2.2
Insertion Loss	Pump Channel@ λ_2	dB	≤1.0	
Signal Tap Ratio		%	1±0.5, 2±0.7, 5±1, 10, 20, 30, 40, 50	
Signal Isolation (Signal Channel@ λ_1 , 23°C)		dB	≥16	≥35
Wavelength Isolation	Signal Channel@ λ_2	dB	≥25	
	Pump Channel@ λ_1	dB	≥12	
Optical Return Loss		dB	≥45	
Extinction Ratio		dB	≥18	
Pump Type	S Type	-	Forward Pump, Only Slow Axis Working	
	F Type	-	Forward Pump, Both Axis Working	
	B Type	-	Backward Pump, Only Slow Axis Working	
Fiber Type	Common & Signal Port	-	PM1550 Panda Fiber or PM1950 Fiber (V)	
		-	10/130um PMDC Fiber (O) or 25/250um PMDC Fiber (R)	
	Pump & Tap Port	-	Same Fiber or Corr. SM Fiber	
Fiber Tensile Load		N	5	
Maximum Optical Power (CW)		mW	300	
Operating Temperature		°C	0~50	
Storage Temperature		°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x40	
	Metal Box	mm	(L)120x(W)12x(H)10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPHT-NN	NN	-	C	C	NN	-	C	C	-(C)	C	C	NN	-	CC/CCC
Pump WL	Signal WL	Stage	Pump Type	Tap Ratio	Pump Fiber	Tap Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type			
53=1530nm	20=2000nm	S=Single Stage	S=S Type	01=1%	P=Same Fiber	P=Same Fiber	M=Metal Box	2=PM1550 Fiber	B=Bare Fiber	05=0.5m	N=Without Connector			
15=1550nm		D=Dual Stage	F=F Type	05=5%	S=Corr. SM Fiber	S=Corr. SM Fiber	Blank for SST	V=PM1950 Fiber	L=Loose Tube	10=1.0m	FC/APC=FC/APC Connector			
57=1570nm			B=B Type	10=10%				0=10/130 PMDC Fiber	2=2mm Cable	15=1.5m	LC/PC=LC/PC Connector			
59=1590nm				50=50%				R=25/250 PMDC Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector			