

915/1053nm WDM/Isolator/Tap PM Hybrid for Pulse Power

FEATURES

- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks

SPECIFICATIONS

Parameters	Unit	Single Stage	Dual Stage
Signal Wavelength Range λ_1	nm	1053+/-10	
Pump Wavelength Range λ_2	nm	915+/-10	
Excess Loss@23°C Signal Channel@ λ_1	dB	≤3.6	≤5.1
Insertion Loss@23°C Pump Channel@ λ_2	dB	≤1.0	
Signal Tap Ratio	%	1+/-0.5%, 2+/-0.7%, 5+/-1.0%, 10%, 20%, 30%, 50%	
Signal Isolation (23°C, All SOP)	dB	≥25	≥45
Wavelength Isolation	Signal Channel@ λ_2	≥25	
	Pump Channel@ λ_1	≥12	
Optical Return Loss	dB	≥45	
Extinction Ratio	dB	≥18	
Pump Direction	S Type	-	Forward Pump, Only Slow Axis Working
	F Type	-	Forward Pump, Both Axis Working
	B Type	-	Backward Pump, Only Slow Axis Working
Fiber Type	Common and Signal Port	-	PM850 Fiber, PM980 Fiber or PM1060L Fiber (E)
		-	10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W)
		-	20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
	Pump Port (915nm)	-	Same Fiber, Corr. SM Fiber, PM850 Fiber, HI780 Fiber, PM980 Fiber (M) or HI1060 Fiber (X)
Tap Port	-	Same Fiber or Corr. SM Fiber	
Fiber Tensile Load	N	5	
Max. Signal Average Power	mW	200	
Max. Pump Average Power	W	0.3, 0.5, 1, 2, 3, 5, 10	
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x40
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPHT-9105-**C** **C** **NN** - **C** **C** - **H** **NN** **P** **NN** - (**NN**) - (**C**) **C** **C** **NN** - **CC/CCC**

Stage	Pump Type	Tap Ratio	Pump Fiber	Tap Port Fiber	Average Power	Peak Power	Pump Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
S= Single	S= S Type	01= 1%	P=PM850 Fiber	P=Same Fiber	02=200mW	01=100W	05=500mW	M= Metal Box	2=PM850Fiber	B= Bare fiber	05=0.5m	N=Without Connector
D= Dual	F= F Type	05=5%	Y=Same Fiber	S=Corr. SM Fiber		1= 1kW	1=W	Blank for SST	H=PM980 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	B= B Type	10=10%	S=Corr. SM Fiber			10= 10kW	10=W		E=PM1060L Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
		50=50%	H=HI780 Fiber			20=20kW	Blank for 300mW		R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/APC Connector

